

APX™ 8000H

ALL-BAND P25 HAZLOC PORTABLE RADIO

APX 8000 SERIES

360 DEGREES OF PROTECTION

YOUR OFFICERS WILL STOP AT NOTHING TO KEEP THE COMMUNITY SAFE. GIVE THEM THAT SAME PROTECTION WITH THE APX 8000H, OUR MOST ADVANCED RADIO EVER.

We know the job puts your officers in harm's way every day. The last thing they need to worry about is safe communication. Certified to the stringent Div1 HazLoc standards, the APX 8000H is designed for use in areas where there are routinely dangerous concentrations of flammable gases, vapors, liquids or combustible dust. No heat. No sparks. No worries.

Of course, communication matters too. Your officers can't afford not to hear—or be heard. The APX 8000H has an adaptive audio engine that provides the loudest, clearest audio at any volume, in any environment. We also know that they need to connect with outside agencies, often without a moment to spare. The APX 8000H transmits and receives on all commonly used frequencies, so they can communicate with different agencies using the same radio. With its intuitive design and comfortable feel, the APX 8000H is made for the way your officers work.

-  RESPOND WITH CONFIDENCE
-  ALL BANDS, NO BOUNDARIES
-  SOUND MATTERS
-  CONQUER CHAOS
-  MADE FOR THE MISSION
-  ALL THE SUPPORT YOU NEED





RESPOND WITH CONFIDENCE

Certified to Div1 HazLoc standards, the APX 8000H is safe to use in areas where there are concentrations of flammable gasses, vapors, liquids, or combustible dust.



SOUND MATTERS

Your officers can't afford not to hear—or be heard. The APX 8000H adaptive audio engine gives you the loudest, clearest audio in any environment.



MADE FOR THE MISSION

With its intuitive design and comfortable feel, the APX 8000H is made specifically for the way your officers work and communicate.



ALL BANDS, NO BOUNDARIES

The APX 8000H transmits and receives on all commonly-used frequencies, so your officers can communicate with different agencies using the same radio.



CONQUER CHAOS

With a water-tight seal, drop-resistant dual battery latch, pressure-tested tempered glass display and a shock-absorbing aluminum alloy endoskeleton, the APX 8000H is built to survive everything from drops to drownings.



ALL THE SUPPORT YOU NEED

Motorola Solutions offers three levels of service plans—Premier, Advanced, and Essential—so you can manage in the way that suits you best.

T-Grip shape for secure carry

Ergonomic emergency button

Multi-microphone noise cancellation

Full color front display

Available with full or limited keypad

Accessory connector with water / dust seal

Recess for custom labeling

HazLoc battery

Standard all-band antenna

Top display for on-belt status updates

Angled volume knob for ease of access

Waterproof speaker with 5 W of audio power

Non-slip PTT button

3x side programmable buttons



FEATURES

OPERATION MODES

Digital Trunking: 9600 Baud APCO P25 Phase 1 FDMA and Phase 2 TDMA

Analog Trunking: 3600 Baud SmartNet®, SmartZone®, Omnilink

Digital Conventional: APCO 25

Analog Trunking: MDC 1200, Quik Call II

ASTRO 25 Integrated Voice and Data

MODELS AVAILABLE

All-band: VHF, UHF (ranges 1 and 2), 700 and 800 MHz

CONNECTIVITY

Mission-Critical Bluetooth (version 4.0)

Wi-Fi (802.11b/g/n)¹

Data Modem Collaboration over Wi-Fi¹

AUDIO FEATURES

3 W Speaker with Adaptive Equalization

Adaptive Dual-sided Operation

Adaptive Noise Suppression Intensity

Adaptive Gain Control

Adaptive Windporting

Compatible with IMPRES 2 Audio Accessories²

MANAGEMENT

Customer Programming Software (CPS), version R12.00.00 or later

Radio Management

Over-the-air Programming (OTAP)¹

SAFETY

Location-Tracking (GPS and GLONASS)

Mission-critical Geofence¹

Man Down¹

HAZLOC (UL/CSA)

Class I, Div 1, Groups C³, D

Class I, Div 2, Groups A, B, C, D

Class II, Div 1, Group E, F, G

Class III; T3C.³

³Groups C only applies to UL

SECURITY

Single-key ADP Encryption

Software Key

P25 Authentication¹

Multikey for 128 keys and multi-algorithm¹

Over-the-air Rekeying (OTAR)¹

INGRESS PROTECTION

IP68 submersion (2 m, 2 hr)

MIL-STD Delta-T, IP68 (2 m, 4 hr)¹

OTHER FEATURES

Text Messaging

Voice Announcements

Radio Profiles

Dynamic Zone

Intelligent Lighting

IMPRES 2 Battery

RFID Volume Knob¹

Digital Tone Signaling¹

Instant Recall

Intelligent Priority Scan

SRX PACKAGE FEATURES**

Coyote Brown Color

NVG Compatibility

Light Discipline Lens

Blacked-out Logo

MIL-STD Delta-T, IP68 (2 m, 4 hr)

** For critical communications in military applications, such as installation security and force protection, we offer an optional SRX package.

DIMENSIONS

RADIO WITHOUT BATTERY

Height (radio body)	6.1 in	154 mm
Width	3.0 in	76 mm
Depth	1.6 in	41 mm
Weight	12.9 oz	367 g

RADIO WITH STANDARD BATTERY

Height (radio body)	6.3 in	160 mm
Width	3.0 in	76 mm
Depth	1.9 in	49 mm
Weight	20.0 oz	568 g



¹ Optional.

² Review accessory catalog and UL manual for more details.

³ Per Underwriters' Laboratory TIA4950. Review UL manual for more details.



RADIO MODELS

	MODEL 3.5	MODEL 2.5
Display	Full bitmap color LCD front display <ul style="list-style-type: none"> • 2 lines of status icons • 4 lines of text x 14 characters • 1 line of menu x 3 keys • White backlight 	Full bitmap color LCD front display <ul style="list-style-type: none"> • 2 lines of status icons • 4 lines of text x 14 characters • 1 line of menu x 3 keys • White backlight
	Full bitmap mono LCD top display <ul style="list-style-type: none"> • 1 line of text x 8 characters • 1 line of status icons • Multi-color backlight 	Full bitmap mono LCD top display <ul style="list-style-type: none"> • 1 line of text x 8 characters • 1 line of status icons • Multi-color backlight
Keypad	4x3 keypad	-
	3 soft keys	3 soft keys
	4-way navigation pad	4-way navigation pad
	Home key	Home key
	Data key	Data key
Channel Capacity	3000	3000
FLASHport Memory	2 GB	2 GB
Part Number	H91TGD9PW9AN	H91TGD9PW8AN
Buttons and Switches	Non-slip PTT button	Non-slip PTT button
	Emergency button (orange)	Emergency button (orange)
	Power / volume knob (angled)	Power / volume knob (angled)
	Rotary selector, 16-position	Rotary selector, 16-position
	Concentric switch, 2-position	Concentric switch, 2-position
	A/B/C switch, 3-position	A/B/C switch, 3-position
	3 programmable side buttons	3 programmable side buttons





TRANSMITTER

	VHF	UHF 1	UHF 2	700MHz	800MHz
Frequency Range / Bandsplits	136-174 MHz	380-470 MHz	450-520 MHz	762-776, 794-806 MHz	806-825, 851-870 MHz
Channel Spacing ¹	12.5 / 20 / 25 kHz	12.5 / 20 / 25 kHz	12.5 / 20 / 25 kHz	12.5 / 20 / 25 kHz	12.5 / 20 / 25 kHz
Maximum Frequency Separation	Full Bandsplit	Full Bandsplit	Full Bandsplit	Full Bandsplit	Full Bandsplit
Rated RF Output Power (Adjustable) ²	1-6 W	1-5 W	1-5 W	1-2.5 W	1-3 W
Frequency Stability (-30 °C to +60 °C; +25 °C Ref.) ²	±1.0 ppm	±1.0 ppm	± 1.0 ppm	± 1.0 ppm	± 1.0 ppm
Modulation Limiting (12.5 / 20 / 25 kHz channel) ²	±2.5 / ±4 / ±5 kHz	±2.5 / ±4 / ±5 kHz	±2.5 / ±4 / ±5 kHz	±2.5 / ±4 / ±5 kHz	±2.5 / ±4 / ±5 kHz
Emissions (conducted and radiated) ²	-75 dBc	-75 dBc	-75 dBc	-75 dBc	-75 dBc
Audio Response ²	+1, -3 dB	+1, -3 dB	+1, -3 dB	+1, -3 dB	+1, -3 dB
FM Hum and Noise (12.5 / 25 kHz channel) ²	-51 / -51 dB	-51 / -51 dB	-47 / -51 dB	-47 / -49 dB	-46 / -49 dB
Audio Distortion (12.5 / 25 kHz channel) ²	0.90% / 0.50%	0.90% / 0.50%	0.90% / 0.60%	0.90% / 0.90%	0.90% / 0.60%

RECEIVER

	VHF	UHF 1	UHF 2	700MHz	800MHz
Frequency Range / Bandsplits	136-174 MHz	380-470 MHz	450-520 MHz	762-776MHz	851-870 MHz
Channel Spacing ¹	12.5 / 20 / 25 kHz	12.5 / 20 / 25 kHz	12.5 / 20 / 25 kHz	12.5 / 20 / 25 kHz	12.5 / 20 / 25 kHz
Maximum Frequency Separation	Full Bandsplit	Full Bandsplit	Full Bandsplit	Full Bandsplit	Full Bandsplit
Audio Output at Rated ²	3 W	3 W	3 W	3 W	3 W
Audio Output at Max ²	5 W	5 W	5 W	5 W	5 W
Frequency Stability (-30 °C to +60 °C; +25 °C Ref.) ²	±1.0 ppm	±1.0 ppm	±1.0 ppm	±1.0 ppm	±1.0 ppm
Analog Sensitivity (12 dB SINAD) Standard ²	0.168 µV (-122.5 dBm)	0.199 µV (-121.0 dBm)	0.199 µV (-121.0 dBm)	0.224 µV (-120.0 dBm)	0.224 µV (-120.0 dBm)
Digital Sensitivity (1% BER) ³	0.251 µV (-119.0 dBm)	0.282 µV (-118.0 dBm)	0.282 µV (-118.0 dBm)	0.316 µV (-117.0 dBm)	0.316 µV (-117.0 dBm)
Digital Sensitivity (5% BER) ³	0.149 µV (-123.5 dBm)	0.158 µV (-123.0 dBm)	0.158 µV (-123.0 dBm)	0.211 µV (-120.5 dBm)	0.211 µV (-120.5 dBm)
Selectivity (12.5 / 25 kHz channel) ²	-77 / -82 dB	-74 / -80 dB	-74 / -80 dB	-72 / -79 dB	-72 / -78 dB
Intermodulation (12.5 / 25 kHz channel) Standard ²	-82 dB	-80 dB	-80 dB	-81 dB	-80 dB
Spurious Rejection ²	-92 dB	-98 dB	-98 dB	-98 dB	-98 dB
FM Hum and Noise (12.5 / 25 kHz channel) ²	-55 / -57 dB	-54 / -56 dB	-54 / -56 dB	-53 / -55 dB	-52 / -54 dB
Audio Distortion ²	0.90%	0.90%	0.90%	0.90%	0.90%

BATTERIES

Part No	Type	Capacity	HazLoc	Dimensions	Weight	Availability
PMNN4547	Li-Ion IMPRES 2	3100 mAh	Y	3.4 x 2.3 x 1.8 in (86 x 59 x 45 mm)	7.1 oz (201 g)	Standard

¹Please refer to local regulations for available channel bandwidths.

²Measured conductively in analog mode per TIA / EIA 603 under nominal conditions.

³Measured conductively in digital mode per TIA / EIA IS 102.



ENCRYPTION

Supported Encryption Algorithms	ADP, 256-bit AES, DES, DES-XL, DES-OFB, DVP-XL, Localized Algorithm
Encryption Algorithm Capacity	8
Encryption Keys per Radio	1024 keys Programmable for 128 Common Key References (CKR) or 16 Physical Identifiers (PID)
Encryption Frame Re-sync Interval	360 ms (P25 CAI)
Encryption Keying	Local Key Loader and Over the Air Rekeying (OTAR)
Synchronization	XL – Counter Addressing OFB – Output Feedback
Vector Generator	National Institute of Standards and Technology (NIST) approved random number generator
Encryption Type	Digital and SecureNet
Key Storage	Tamper-protected volatile or non-volatile memory
Key Erasure	Keyboard command and tamper detection
Standards	FIPS 140-2 Level 3 FIPS 197

GPS

Constellations	GPS and GLONASS
Tracking Sensitivity	-164 dBm
Accuracy ¹	<5 meters (95%)
Cold Start ¹	<60 seconds (95%)
Hot Start ¹	<5 seconds (95%)
Mode of Operation	Autonomous (Non-Assisted)

WIRELESS

Bluetooth®
Frequency Range: 2402 - 2480 MHz
Mission Critical Wireless Bluetooth 4.0 uses 96 bit encryption for pairing and 128 bit encryption for voice, signaling and data. The radio supports up to 6 data connections and 1 audio connection
Bluetooth Low Energy uses 128-bit AES-CCM encryption
WLAN
Wi-Fi® 802.11 b/g/n
Frequency Range: 2400 - 2483.5 MHz
Supports WPA-2, WPA, WEP security protocols
Radio can be pre-provisioned with up to 20 SSIDs

AUDIO

Audio Output at Rated	3 W
Audio Output at Max	5 W
Audio Response (EIA)	+1, -3 dB
Speech Loudness at 12 in (300 mm)	105 phon
Audio Features	Adaptive Equalization Adaptive Dual-sided Operation Adaptive Noise Suppression Intensity Adaptive Gain Control Adaptive Windporting IMPRES 2 Audio

OTHER OPTIONS

Housing Color Options	Standard: Black SRX Package: Coyote Brown
-----------------------	--



REGULATORY INFORMATION

FCC ID	All-Band	AZ489F7111
IC ID	All-Band	109U-89F7111
Emission Designators	LMR	8K10F1D, 8K10F1E, 8K10F1W, 11K0F3E, 16K0F3E, 20K0F1E
	Bluetooth	852KF1D, 1M17F1D, 1M19F1D
	WLAN (Wi-Fi)	13M7G1D, 17MOD1D, 18M1D1D

ENVIRONMENTAL

Operating Temperature	-20 to +60 °C (-20 to +140 °F)
Storage Temperature ¹	-40 to +85 °C (-40 to +185 °F)
Humidity	Per MIL-STD 810
ESD	IEC 801 - 2 kV
Dust Resistance	IP6X
Water Resistance	(Submersion) IPX8 (2 meters, 2 hours); Optional Mil Std (Delta-T) and IPX8 (2 meters, 4 hours)
Leakage (Immersion)	MIL-STD-810 C, D, E, F and G

MIL-STD

	MIL-STD 810C		MIL-STD 810D		MIL-STD 810E		MIL-STD 810F		MIL-STD 810G	
	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.	Method	Proc./Cat.
Low Pressure	500.1	I	500.2	II	500.3	II	500.4	II	500.5	II
High Temperature	501.1	I,II	501.2	I/A1, II/A1	501.3	I/A1, II/A1	501.4	I/Hot, II/Hot	501.5	I/A1, II/A1
Low Temperature	502.1	I	502.2	I/C3, II/C1	502.3	I/C3, II/C1	502.4	I/C3, II/C1	502.5	I/C3, II/C1
Temperature Shock	503.1	I	503.2	I/A1/C3	503.3	I/A1/C3	503.4	I	503.5	I-C
Solar Radiation	505.1	II	505.2	I	505.3	I	505.4	I	505.5	I/A1
Rain	506.1	I,II	506.2	I,II	506.3	I,II	506.4	I,III	506.5	I,III
Humidity	507.1	II	507.2	II	507.3	II	507.4	1 Proc	507.5	II/Aggravated
Salt Fog	509.1	I	509.2	I	509.3	I	509.4	1 Proc	509.5	1 Proc
Blowing Dust	510.1	I	510.2	I	510.3	I	510.4	I	510.5	I
Explosive Atmosphere	-	-	511.2	I	511.3	I	511.4	I	511.5/6	I
Blowing Sand	1 Proc	1 Proc	510.2	II	510.3	II	510.4	II	510.5	II
Submersion ²	512.1	I	512.2	I	512.3	I	512.4	I	512.5	I
Submersion (Salt Water) ²	512.1	I	512.2	I	512.3	I	512.4	I	512.5	I
Vibration	514.2	VIII,F, Curve-W	514.3	I/10, II/3	514.4	I/10, III/3	514.5	I/24, II/5	514.6	I/24, II/5
Shock	516.2	I, V	516.3	I, VI	516.4	I, VI	516.5	I, VI	516.6	I, VI
Shock (Drop)	516.2	II	516.2	IV	516.4	IV	516.5	IV	516.6	IV

¹ Radio only. To ensure best performance, batteries should be stored at 25 °C, ±5 °C.

² Submersion tests conducted using the more stringent, preheated (Delta-T) product method is available as an optional feature.



ACHIEVE MISSION CRITICAL PERFORMANCE WITH MANAGED AND SUPPORT SERVICES

RISK & RESPONSIBILITY



ENSURE CONTINUITY • ENHANCE PRODUCTIVITY • REDUCE RISK.

ESSENTIAL

Only Support When You Need It

When the unpredictable happens to your network, Essential Services provide you access to Motorola's Technical Support teams and resources for troubleshooting and maintenance.

ADVANCED

Improve Response and Continuity

Motorola's expert service teams help mitigate downtime and ensure network continuity. Get fast response to network issues by our qualified technicians who analyze and diagnose your network as well as deliver routine maintenance.

PREMIER

Maximize Performance and Reduce Risk

Motorola's Managed Services team helps operate and optimize your mission critical system. With Premier Services, you fully transfer the risk to Motorola and ensure your system operates at maximum performance levels, allowing your team to keep focus on its primary responsibilities.

For more information, please visit: www.motorolasolutions.com/apx



Motorola Solutions, Inc. 500 West Monroe Street, Chicago, IL 60661 U.S.A. www.motorolasolutions.com

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © 2019 Motorola Solutions, Inc. All rights reserved. 11-2019